

The APB-500B8 of the new **VALUE SERIES** offers both quality and **80 PLUS® 230V EU** efficiency at a highly competitive pricing. Equipped with a vast amount of required connectors, long native cables and a silent running fan with installed thermal board, the PSU runs quietly on full load and provides **REAL POWER**, thereby providing all security features. Certified by **CE, CB, EAC, TÜV** and amongst many others, it's the **VALUE** choice!








| Technical data                |   |
|-------------------------------|---|
| Model                         | Value 500W  |
| Artikel no.                   | APB-500B8   |
| EAN code                      | 4710713230569   |
| Weight (without/with package) | 1.22 kg / 1.35 kg   |
| Specification                 | ATX 12V 2.3   |
| Form factor                   | PS II   |
| Efficiency                    | 80 PLUS® 230V EU  |
| PFC                           | Active PFC (0.9) (only 230V)  |
| Fan                           | 120mm silent fan  |
| Dimension (DxWxH)             | 140mm x 150mm x 87mm  |
| Security                      | AFC (Automatic Fanspeed Control)<br>OPP (Overload Protection)<br>OVP (Overvoltage Protection)<br>SCP (Short-circuit Protection)<br>SIP (Surge & Inrush Protection)<br>UVP (Undervoltage Protection) |
| Warranty                      | 24 Months   |

| Output data |                     |                     |      |      |      |       |
|-------------|---------------------|---------------------|------|------|------|-------|
| Value 500W  | AC Input            | 200-240V 47-63Hz 4A |      |      |      |       |
|             | DC Output           | +3.3V               | +5V  | +12V | -12V | +5VSB |
|             | Max. Current        | 18A                 | 17A  | 38A  | 0.3A | 2.5A  |
|             | Max. Combined Power | -                   |      | 456W | 3.6W | 12.5W |
|             |                     |                     | 500W |      |      |       |

\* The listed specifications may be altered at any point in time without any pre-notice.

\*\* Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

|   | Cable             | Connectors | Length (mm) |
|---|-------------------|------------|-------------|
|    | 20+4 PIN ATX      | 1          | 500         |
|    | 8 PIN EPS (4+4)   | 1          | 350         |
|    | 8 PIN PCI-E (6+2) | 1          | 350         |
|    | MOLEX             | 2          | 350/150/150 |
|   | FLOPPY            | 1          |             |
|  | SATA              | 3          | 350/150/150 |

Certification



\* The listed specifications may be altered at any point in time without any pre-notice.

\*\* Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.